EKA | CyberLock®

CyberBox

Part number: BLR-BOX-01

CyberBox is a keyless lock box that provides secure storage for items such as mechanical keys, access cards, and more. It can be effortlessly opened using virtually any Bluetooth-enabled mobile device, providing the convenience, security and reliability demanded by a wide array of industries.

CyberBox is available in shackle or wall-mounted configurations, as well as an over-the-door mounting option.

Advanced Keyless Security

Bluetooth 5.0 technology and CMAC-AES256 challenge-response authentication protect valuable assets against unauthorised access attempts. An item sensor in the storage compartment enables tracking when a single item is removed and returned to the box. This information can be logged in an audit trail.

Real-Time Control

Administrators can issue on-demand credentials to contractors, employees and authorised visitors through CyberLock's powerful software suite, CyberAudit-Web. Users can rapidly obtain their permissions using the Cyber Access app to gain access to CyberBox.

Flexible Access Options

Optimise user efficiency with multiple credential options. Send keyless credentials to Android and iOS devices through the Cyber Access app. Alternatively, issue physical credentials such as an IR fob or compatible CyberKey for added flexibility.

eka | ⊙ **CyberLock**®

CyberBox Wall Mount

Part number: BLR-BOX-01

CAW	Version 9.9 or newer
Enterprise	☑
Basic	☐

CyberBox is a keyless lockbox that facilitates access control using a Bluetooth enabled device. Provides storage for keys, access cards, and more. An item sensor indicates when the stored item is present.

Specifications

|	
Physical	Powder-coated aluminum box, polycarbonate
Operating Temperatures	-4° to 140° F (-20° to 60° C)
	Below 14° F (-10° C), battery capacity significantly reduced*
Dimensions	5.8" L x 3.4" W x 2.44" H (147 mm x 86 mm x 62 mm)
Weight	46 oz (1,304 g)
Power	4AA batteries, field replaceable (supplied with alkaline, lithium recommended for cold weather)
Visual Indicators	2 multicolored LED indicator lights
Audio Indicator	Beeper
Access Options	Cell phone with app, IR with fob, CK-FLASH, CK-AIR2, CKR-BLUE3
Management Options	IR Encoder 10 (CKBR-IR10), Bluetooth mobile device
Software	CyberAudit® Enterprise 9.9 (or newer)
Battery Life	Up to 2 years depending on usage
RoHS	Compliant with EU 2015/863
IP Rating	IP54

Notes:
Dimensions in mm
Drawing not to scale
Ø indicates diameter