

The field replaceable EL123 lithium battery ensures continued functionality with a lifespan of up to 5 years.



Advanced Keyless Security

Near Field Communication (NFC) and CMAC AES-256 challenge-response authentication ensures the security of critical assets, providing protection against unauthorised access attempts.



Robust Design

With weather-resistant, IP-68 rated durability, the NFC padlock can withstand water, dust, and dirt, ensuring reliable performance even in the most challenging environments.



Real-Time Control

Administrators can issue on-demand credentials to contractors, employees, and authorized visitors through CyberLock's powerful software suite, CyberAudit-Web. When changes occur, users can rapidly update their permissions using the Cyber Access app to enable access to the lock.



Flexible Access Options

Optimize user efficiency with multiple credential options. Send keyless credentials to Android and iOS devices through the Cyber Access app. Alternatively, issue physical credentials such as an IR fob or compatible CyberKey for added flexibility.





CyberLock NFC Padlock, 2" Shackle

Part number: NFCR-PL02

CAW	Version 9.9 or newer
Enterprise	\checkmark
Basic	

The CyberLock NFC (Near Field Communication) padlock is a keyless lock that facilitates access control using an NFC-enabled device.

Specifications

Physical Brass, stainless steel, and polycarbonate

-4° to 140° F (-20° to 60° C) below 14° F (-10° C) battery capacity is significantly reduced **Operating Temperatures**

> 34.7 oz (984 g) Weight

6.09" L x 2.24" W x 1.5" H (154.7 mm x 56.9 mm x 38.1 mm) **Dimensions**

Communication Infrared, NFC

Visual Output Multicolor LED indicator light

> EL123 lithium battery, field replaceable Power

Cyber Access app on Android or iOS, CK-FLASH, CK-AIR2, CKR-BLUE3, FK-01 IR Fob **Access Options**

Programming and Download Options CyberLink 2 on PC or CyberAudit Link Android via CKBR-IR10 IR Encoder 10

> CyberAudit® Enterprise 9.9 (or newer) Software

Battery Life Up to 5 years

Audit Capacity Up to 6,460 open/lock events

> Compliant with EU 2015/863 RoHS

IP68 IP Rating



